

Film and Foil Capacitors with Mixed Dielectric for Pulse Applications PCM 7.5 mm to 15 mm

Special Features

- Pulse duty construction
- Constant capacitance value versus temperature (similar to the obsolete Polycarbonate)
- Low dissipation factor
- According to RoHS 2002/95/EC

Typical Applications

For general DC-applications requiring a high capacitance stability versus temperature e.g.

- Automotive electronics
- Lighting

Construction


Dielectric:

Mixed film

Capacitor electrodes:

Metal foil

Internal construction:



Encapsulation:

Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0

Terminations:

Tinned wire.

Marking:

Colour: Red. Marking: Black.

Epoxy resin seal: Yellow.

Electrical Data

Capacitance range:

1000 pF to 0.1 μ F (E12-values on request)

Rated voltages:

100 VDC, 250 VDC, 400 VDC, 630 VDC

Capacitance tolerances:

$\pm 20\%$, $\pm 10\%$, $\pm 5\%$

Operating temperature range:

-55°C to +100°C

Climatic test category:

55/100/56 in accordance with IEC

Insulation resistance

at +20°C: $\geq 5 \times 10^5 \Omega$

(mean value: $1 \times 10^6 \Omega$)

Measuring voltage: 100 V/1 min.

Test voltage:

$2 U_r$, 2 sec.

Dissipation factors

at f	$C \leq 0.1 \mu F$
1 kHz	$\leq 3 \times 10^{-3}$
10 kHz	$\leq 5 \times 10^{-3}$
100 kHz	$\leq 8 \times 10^{-3}$

Maximum pulse rise time:

1000 V/ μ sec for pulses equal to the rated voltage

Mechanical Tests

Pull test on leads:

10 N in direction of leads according to IEC 60068-2-21

Vibration:

6 hours at 10 ... 2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6

Low air density:


1kPa = 10 mbar in accordance with IEC 60068-2-13

Bump test:

4000 bumps at 390 m/sec^2 in accordance with IEC 60068-2-29

Capacitance change versus temperature

($f = 1 \text{ kHz}$) (general guide)



Voltage derating:

A voltage derating factor of 1.35 % per K must be applied from +85°C for DC voltages and from +75°C for AC voltages

Reliability:

Operational life > 300 000 hours
Failure rate < 5 fit ($0.5 \times U_r$ and 40°C)

Packing

Available taped and reeled.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

Continuation

General Data

Capacitance	100 VDC/63 VAC*				250 VDC/160 VAC*				400 VDC/250 VAC*				630 VDC/300 VAC*			
	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**
1000 pF	3	8.5	10	7.5	3	8.5	10	7.5	3	9	13	10	5	11	13	10
1500 "	3	8.5	10	7.5	3	8.5	10	7.5	3	9	13	10	5	11	13	10
2200 "	3	8.5	10	7.5	4	9	10	7.5	3	9	13	10	6	12	13	10
3300 "	3	8.5	10	7.5	4	9	10	7.5	3	9	13	10	6	12	13	10
4700 "	4	9	10	7.5*	3	9	13	10	4	9.5	13	10	6	12	13	10
	3	9	13	10*												
6800 "	4	9	10	7.5*	4	9.5	13	10	5	11	13	10	5	11	18	15
	4	9.5	13	10*												
0.01 μ F	4	9.5	13	10	4	9.5	13	10	6	12	13	10	6	12.5	18	15
0.015 "	4	9.5	13	10	5	11	13	10	6	12.5	18	15	7	14	18	15
0.022 "	5	11	13	10	6	12	13	10	6	12.5	18	15	8	15	18	15
0.033 "	6	12	13	10	6	12.5	18	15	7	14	18	15	9	16	18	15
0.047 "	6	12.5	18	15	7	14	18	15	9	16	18	15				
0.068 "	7	14	18	15	9	16	18	15								
0.1 μ F	9	16	18	15												

* AC voltage: $f \leq 400$ Hz; $1.4 \times U_{rms} + U_{DC} \leq U_r$


** PCM = Printed circuit module = lead spacing

* On ordering please state the required PCM (lead spacing)!


If not specified, smaller PCM will be booked.

Dims. in mm.

Taped version see page 104.







$d = 0.5 \varnothing$ if $W = 3$ } PCM 7.5 and 10
 $d = 0.6 \varnothing$ if $W \geq 4$
 $d = 0.8 \varnothing$ if PCM = 15



Impedance change with frequency (general guide).

Rights reserved to amend design data without prior notification.

Permissible AC voltage in relation to frequency at $10^\circ C$ internal temperature rise (general guide).



Recommendation for Processing and Application of Through-Hole Capacitors

Soldering Process

A preheating of through-hole WIMA capacitors is allowed for temperatures $T_{max} < 100^\circ C$.

In practice a preheating duration of $t < 5$ min. has been proven to be best.



Single wave soldering

Soldering bath temperature: $T < 260^\circ C$
Immersion time: $t < 5$ sec

Double wave soldering

Soldering bath temperature: $T < 260^\circ C$
Immersion time: $2 \times t < 3$ sec

Wave soldering



Temperature/time graph for the maximum permissible solder bath temperature for the wave soldering of through-hole WIMA capacitors

WIMA Quality and Environmental Philosophy

ISO 9001:2000 Certification

ISO 9001:2000 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2000 of our factories by the VDE inspectorate certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

WIMA WPSCS

The WIMA Process Control System (WPSCS) is a quality surveillance and optimization system developed by WIMA. WPSCS is a major part of the quality-oriented WIMA production. Points of application of WPSCS during production process:

- **incoming material inspection**
- **metallization**
- **film inspection**
- **schoopage**
- **pre-heating**
- **lead attachment**
- **cast resin preparation/ encapsulation**
- **100% final inspection**
- **AQL check**

WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

<ul style="list-style-type: none"> – Lead – PCB – CFC – Hydrocarbon chloride – Chromium 6+ 	<ul style="list-style-type: none"> – PBB/PBDE – Arsenic – Cadmium – Mercury – etc.
--	--

We merely use pure, recyclable materials for packing our components, such as:

- **carton**
- **cardboard**
- **adhesive tape made of paper**
- **polystyrene**

We almost completely refrain from using packing materials such as:

- **foamed polystyrene (Styropor®)**
- **adhesive tapes made of plastic**
- **metal clips**

RoHS Compliance

According to the RoHS Directive 2002/95/EC certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei
konform RoHS 2002/95/EG

WIMA capacitors are lead free
in accordance with RoHS 2002/95/EC

Tape for lead-free WIMA capacitors

DIN EN ISO 14001:2005

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2005. The certification has been granted in June 2006.

Typical Dimensions for Taping Configuration




Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5*mm

*PCM 27.5 taping possible with two feed holes between components

Designation	Symbol	Dimensions for Radial Taping						
		PCM 2.5 taping	PCM 5 taping	PCM 7.5 taping	PCM 10 taping*	PCM 15 taping*	PCM 22.5 taping	PCM 27.5 taping
Carrier tape width	W	18.0 ± 0.5	18.0 ± 0.5	18.0 ± 0.5	18.0 ± 0.5	18.0 ± 0.5	18.0 ± 0.5	18.0 ± 0.5
Hold-down tape width	W ₀	6.0 for hot-sealing adhesive tape	6.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape
Hole position	W ₁	9.0 ± 0.5	9.0 ± 0.5	9.0 ± 0.5	9.0 ± 0.5	9.0 ± 0.5	9.0 ± 0.5	9.0 ± 0.5
Hold-down tape position	W ₂	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.			
Feed hole diameter	D ₀	4.0 ± 0.2	4.0 ± 0.2	4.0 ± 0.2	4.0 ± 0.2	4.0 ± 0.2	4.0 ± 0.2	4.0 ± 0.2
Pitch of component	P	12.7 ± 1.0	12.7 ± 1.0	12.7 ± 1.0	25.4 ± 1.0	25.4 ± 1.0	38.1 ± 1.5	38.1 ± 1.5 or 50.8 ± 1.5
Feed hole pitch	P ₀	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ± 0.3 cumulative pitch error max. 1.0 mm/20 pitch
Feed hole centre to lead	P ₁	5.1 ± 0.5	3.85 ± 0.7	2.6 ± 0.7	7.7 ± 0.7	5.2 ± 0.7	7.8 ± 0.7	5.3 ± 0.7
Hole centre to component centre	P ₂	6.35 ± 1.3	6.35 ± 1.3	6.35 ± 1.3	12.7 ± 1.3	12.7 ± 1.3	19.05 ± 1.3	19.05 ± 1.3
Feed hole centre to bottom edge of the component	H _▲	16.5 ± 0.3	16.5 ± 0.3	16.5 ± 0.5	16.5 ± 0.5	16.5 ± 0.5	16.5 ± 0.5	16.5 ± 0.5
Feed hole centre to top edge of the component	H ₁	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 24.5 to 31.5	H+H _{component} < H ₁ 25.0 to 31.5	H+H _{component} < H ₁ 26.0 to 37.0	H+H _{component} < H ₁ 30.0 to 43.0	H+H _{component} < H ₁ 35.0 to 45.0
Lead spacing at upper edge of carrier tape	F	2.5 ± 0.5	5.0 $^{+0.8}_{-0.2}$	7.5 ± 0.8	10.0 ± 0.8	15 ± 0.8	22.5 ± 0.8	27.5 ± 0.8
Lead diameter	d	0.4 ± 0.05	0.5 ± 0.05	$^{+0.05}_{-0.05}$ 0.5 or 0.6 $^{+0.06}_{-0.05}$	$^{+0.05}_{-0.05}$ 0.5 or 0.6 $^{+0.06}_{-0.05}$	0.8 $^{+0.08}_{-0.05}$	0.8 $^{+0.08}_{-0.05}$	0.8 $^{+0.08}_{-0.05}$
Component alignment	Δh	± 2.0 max.	± 2.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.
Total tape thickness	t	0.7 ± 0.2	0.7 ± 0.2	0.7 ± 0.2	0.7 ± 0.2	0.7 ± 0.2	0.7 ± 0.2	0.7 ± 0.2
Package (see also page 105)	▲	ROLL/AMMO		AMMO				
		REEL $\varnothing 360$ max. $\varnothing 30 \pm 1$	B 52 ± 2 58 ± 2 depending on comp. dimensions	REEL $\varnothing 360$ max. $\varnothing 30 \pm 1$	52 ± 2 B 58 ± 2 or REEL $\varnothing 500$ max. $\varnothing 25 \pm 1$	54 ± 2 B 60 ± 2 68 ± 2 depending on PCM and component dimensions		
Unit		see details page 107.						

▲ Please give „H“ dimensions and desired packaging type when ordering.

Dims in mm.

• Diameter of leads see General Data.

Please clarify customer-specific deviations with the manufacturer.

* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 1). P₀ = 12.7 or 15.0 is possible